

Our innovative High Intensity wide angle Amber LEDs offer the best visibility in all situations

CMS-GP232 & GP465

Full Matrix Truck Mount Changeable Message Sign



GP 232

- Up to 10 Characters per line
- 28 Rows x 72 Columns
- 6 Font Sizes: 5x7W, 7x7, 7x7W, 6x11, 7x20, & 9X20
- 6" - 18" Characters
- 1, 2, or 3 Lines Messages
- Graphics and Animations



GP 465

- 3 lines of up to 12 Characters
- 24 Rows x 48 columns
- 9 Font Sizes: 3x7, 4x7, 5x7, 5x7W, 7x7, 7x7W, 6x11, 7x20, & 9X20
- 11" - 33" Characters
- Graphics, Animations, & Text

SPECIFICATIONS

GENERAL

LED Operating Temp	-22° - +165° F
Electronics Temp. Rating	-30° - +165° F
232 Sign Case Height	34"/0.9m
232 Sign Case Width	71"/1.8m
465 Sign Case Height	48"/ 1.2 m
465 Sign Case Width	78"/2.0 m
Control Console Display	Backlit LCD
Pre-Programmed Messages	199
User-defined Messages	199
Message Sequences	250

LED DISPLAY

Update Speed:	Variable in .10 sec increments
LED Color:	ITE Amber/Yellow 590-592nm
[232] - 1 - 30° LED per pixel,	28 rows x 72 columns
[465] - 4 - 24° LEDs per pixel,	24 rows x 48 columns

OPTIONS

- Remote Control: Cellular, Wireless RF, CDPD, Landline
- Radar Overspeed Detection
- Queue Detection
- NTCIP Compliant / Compatible
- Radar data logging and graphing capability
- Work Zone Alert Radio



2755 Bankers Industrial Dr.
Atlanta, GA 30360
(770)-448-6650 /F (770)-448-8970
www.amsig.com